



Traditional Style Baseboard Heater

PEG Series

Features

Color

- Standard: white.
- Optional (upcharge applicable): almond, metallic silver, bronze, metallic charcoal, aluminum, semi-gloss black, sand.

Finish

- Standard: epoxy/polyester powder coat paint.
- May be repainted with any interior paint.

Voltage

- 240/208V, 1-phase.

Construction

- Robust 22-gauge steel body.
- Sturdy 20-gauge steel front panel.
- Welded 20-gauge steel connection box.
- Rounded corners.
- Linear high-limit temperature control with automatic reset.

Heating element

- Stainless steel tubular heating element with aluminum fins.
- Floating heating element on $\bar{\rm h}$ igh-temperature nylon bushings reducing expansion noises.

Watt density

- Average standard watt density of 275W/ft.

ontrol

- Built-in thermostat kit can be installed at either end.

Global Commander highly recommends using an electronic wall thermostat for greater comfort and efficiency.

Installation

- Installation directly on the floor.
- No need to disassemble for electrical connection or wall attachment.
- Built-in single-screw wire holder on the back for quick connection box access from either end.
- Two rows of oval mounting holes with centering mark for ease of installation.
- Raceway and side knock-outs for baseboard interconnection.

Warranty

- 1-year against defects.
- Lifetime on the heating element.

Application

- Kitchen, living room, family room, bedroom, bay window, commercial building, office building, condo, restaurant.

Models

										Packaging Dimensions					
Product #			Watts	Product Length		Net Weight		Gross Weight		Α		В		С	
Without thermostat	1-pole built-in thermostat¹	2-pole built-in thermostat ¹	240/208V	in.	mm	lb	kg	lb	kg	in.	mm	in.	mm	in.	mm
PEG0300BL I	PEG0300BL-T1CD	PEG0300BL-T2CD	300/225	22 3/4	577	4.5	2.0	4.7	2.1	23	585	2.75	70	6 1/4	159
PEG0500BL I	PEG0500BL-T1CD	PEG0500BL-T2CD	500/375	27 11/16	702	5.4	2.4	5.8	2.5	28	711	2.75	70	6 1/4	159
PEG0750BL	PEG0750BL-T1CD	PEG0750BL-T2CD	750/563	37 11/16	956	7.0	3.2	7.4	3.4	38	965	2.75	70	6 1/4	159
PEG1000BL	PEG1000BL-T1CD	PEG1000BL-T2CD	1000/750	47 15/16	1217	8.7	3.9	9.0	4.1	48 1/4	1226	2.75	70	6 1/4	159
PEG1250BL	PEG1250BL-T1CD	PEG1250BL-T2CD	1250/938	57 7/16	1458	10.7	4.9	11.1	5.1	57 3/4	1467	2.75	70	6 1/4	159
PEG1500BL	PEG1500BL-T1CD	PEG1500BL-T2CD	1500/1125	66 1/8	1679	12.7	5.7	13.1	5.9	66 1/4	1683	2.75	70	6 1/4	159
PEG1750BL	PEG1750BL-T1CD	PEG1750BL-T2CD	1750/1313	75 7/16	1916	13.2	6.0	13.6	6.2	75 3/4	1925	2.75	70	6 1/4	159
PEG2000BL	PEG2000BL-T1CD	PEG2000BL-T2CD	2000/1500	84 1/4	2139	16.2	7.30	16.6	7.5	84 1/4	2139	2.75	70	6 1/4	159
PEG2500BL	PEG2500BL-T1CD	PEG2500BL-T2CD	2500/1875	102 1/4	2596	16.6	7.5	17	7.7	102 1/2	2596	2.75	70	6 1/4	159

Options

Product #	Description
KIT-PEG-T1BL ²	Single-pole bi-metal thermostat: 25A at 120-277V - 10A at 347-600V, with a control knob
KIT-PEG-T2BL ^{2, 3}	Double-pole bi-metal thermostat: 25A at 120-277V - 10A at 347-600V, with a control knob

¹ Factory installed on right end only of the baseboard heater.

Upcharge available for optional colors shown in the color chart section.



²Can be installed on either end of the baseboard heater.

^{3 &}quot;Off" position

Standard color is white