



Requires a grounded
3-pronged outlet



NEMA 6-30R
30A, 250VAC



Portable Heater

CCG Series

Features

Color

- Standard: almond.

Finish

- Standard: epoxy/polyester powder paint.

Voltage

- 240/208V, 1-phase.

Construction

- Handle may be used as a reel for the electric cable.
- 6 ft. (2 m) molded electric cable for extra durability.
- Safely recessed thermostat knob reduces heater size to a minimum.
- High-limit temperature control with automatic reset (first level) and single operation thermal fuse (second level).

Fan

- Totally enclosed motor (-MF model).
- Open motor (-MO model).

Note: The open motor is not intended for use in a dusty environment.

- 300 cfm fan.

Heating element

- Helical coil nickel-chromium alloy wire protected by ceramic insulators.
- Heating element provides instant heat.

Temperature rise

- 28 °C (51 °F).

Control

- Built-in thermostat included.

Installation

- Must be plugged into a grounded 3-pronged outlet, 30A, 250VAC (not supplied).

Note: Always unplug heater when not in use.

Warranty

- 1-year warranty against defects.

Application

- Construction area, workshop, garage.

Models

Product # ¹	Watts 240/208V	Motor type	Net Weight		Gross Weight		Packaging Dimensions						
			lb	kg	lb	kg	A		B		C		
								in.	mm	in.	mm	in.	mm
CCGU4800AM-MF-TB6	4800/3600	Enclosed	16	7.2	16.75	7.3	12 1/2	318	10 1/2	267	14 1/4	362	
CCGU4800AM-MO-TB6	4800/3600	Open	16	7.2	16.75	7.3	12 1/2	318	10 1/2	267	14 1/4	362	

¹Built-in thermostat included.
Standard color is almond.

